



Luminous flux luminaire  
409 lm

Beam Angle: 26°		
h(m)	E(lx)	D(m)
1	1131	0.47
2	283	0.94
3	126	1.41
4	71	1.88
5	45	2.35

## Aqua Aimer 4

Flos

No. FA10526614757

Adjustable spotlight. Configuration: turned and anodized (raw or painted) aluminium structure with stainless steel adjustable bracket. Glass diffuser: transparent or sandblasted with silkscreen border, fixed through a robotic gluing system. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65 In compliance with EN60598-1 standards Class of insulation: III Installation: the luminaire is equipped with 2000mm cable. Aimer 24V is equipped with a dc/dc highly efficient resin-coated converter that removes electromagnetic interference and protects against polarity reversal and sudden voltage peak. Parallel wiring required. Aimer 1 and Aimer RGB require connection in series. We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire. During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating. Damages on the coating exposed to outdoor conditions or water, could cause corrosion. Chemical substances affect the anticorrosion covering protection.

Designed by Flos Outdoor



Polished Stainless Steel

### Technical

Mounting	Projectors,Spike Lights,Wall
Flux	409lm
IP Rating	IP68

### Photometric

Colour Temp	3000K
Dimming	Non Dimmable
Beam Angle	30
CRI	80

### Physical

### Electrical

Power	6.6
Voltage	24
Driver	Remote excluded
Insulation class	III



Our product range updates frequently. All product specifications and data are subject to change without warning in order to improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.