



Luminous flux luminaire  
387 lm

Beam Angle:	14°	
h(m)	E(lx)	D(m)
1	4363	0.23
2	1091	0.47
3	485	0.70
4	273	0.93
5	175	1.17

## Climber Down - 87 Non Dimmable Deep Brown

Flos

No. F1110018

Outdoor wall-mounted luminaire with LED light source. Single downwards emission version. EN AB-47100 aluminium die-cast body with low copper content. Asymmetrical optics housing: the optics in the lower part is retracted and protected by a shield to limit bothersome glare and maximize visual comfort. The micro-texturized glass diffusers are glued to ensure water resistance and texturized to ensure a uniform light beam generated by each individual LED, maintaining excellent lighting efficiency. High-resistance coating: after sandblasting all components to create a porous surface and ensure greater adhesion of the paint, a double layer of external coating is applied according to the QUALICOAT standard. The first layer of epoxy powder confers chemical and mechanical resistance; the second layer, a polyester powder finish, ensures resistance to UV rays and atmospheric agents. The painted surfaces are treated with alkaline and acid washes, then rinsed with demineralized water and subjected to a chemical conversion treatment for rust protection. Integrated 110/240 V power supply. Supplied with an 80-mm length of neoprene cable.

Designed by Piero Lissoni



Deep Brown

### Technical

Mounting	Wall
Flux	387lm
IP Rating	IP65

### Photometric

Colour Temp	2700K
Dimming	Non Dimmable
Beam Angle	14
CRI	80

### Physical

Net Weight (kg)	1.17
-----------------	------

### Electrical

Power	7
Voltage	110-240
Driver	Integrated
Insulation class	I

