



Fenestra 24V Forest Green

Flos

No. F2251012



Luminaire for outdoor use for installation in a window compartment with LED light source. Luminaire body in die-cast aluminum EN AB-47100 (low copper content). High-resistance coating: after a sandblasting treatment of all components to make the surface porous and ensure a greater adhesion of the paint, the external coating is applied with a double layer with epoxy powders according to the QUALICOAT standard. The first layer of epoxy powder gives chemical and mechanical resistance, the second finishing layer of polyester powder ensures resistance to UV rays and atmospheric agents. The painted surfaces are treated with alkaline and acidic washes, then rinsed with demineralized water, subjected to a chemical conversion treatment to protect against oxidation. Thanks to the use of a dual LED source and two laminar emitting lenses, it guarantees a coverage of 270° with homogeneous distribution and excellent color uniformity. UV-stabilized polycarbonate diffuser, silicone seal. Each luminaire is equipped with a mechanical adjustment system to compensate for the inclination of the sills, and to allow the correct orientation of the luminous beam. 12-24V remote power supply to be ordered separately. Equipped with a 1000 mm length outgoing neoprene cable.



Luminous flux luminaire
165 lm

Beam Angle DIR: 10°

h(m)	E(lx)	D(m)
1	320	0.17
2	80	0.34
3	36	0.51
4	20	0.68
5	13	0.85

Designed by Flos Outdoor



Forest Green

Technical

Mounting	Wall,Uplights
Flux	183lm
IP Rating	IP65

Photometric

Colour Temp	3000K
Dimming	Non Dimmable
Beam Angle	151
CRI	80

Physical

Net Weight (kg)	0.50
-----------------	------

Electrical

Power	4
Driver	Remote excluded
Insulation class	III

