

## Flauta H225 Riga

Flos

No. F2340015





Collection of wall-mounted light fittings with dual light emission, available in various lengths. The units are characterised by the surface etching in two refined variations: Flauta Riga, with vertical lines, and Flauta Spiga, characterized by an elegant and sophisticated angular pattern. Rounding out the device is a deflector accessory painted to match the finish of the lamp body. It can be installed as desired on the upper or lower head to create a decorative effect with reflected light. The structure is made of aluminium treated with a chemical conversion process for effective resistance to atmospheric agents. The powder coating of the body is available in various finishes according to the QUALICOAT standard. LED light source included. Integrated 220–240 V electrical power with DALI dimmer. Comes with deflector for optional installation on the upper or lower head. LED light source included. Integrated 220–240 V electrical power with DALI dimmer. Comes with deflector for optional installation on the upper or lower head.

Designed by Patricia Urquiola, 2020



Anodized Copper



Beam Angle: 30°

h(m)	E(lx)	D(m)
1	16629	0.54
2	4157	1.09
3	1848	1.63
4	1039	2.18
5	665	2.72

Luminous flux luminaire  
353 lm

### Technical

Mounting	Wall
Flux	493lm
IP Rating	IP40

### Photometric

Colour Temp	2700K
Dimming	Push,DALI
CRI	95
Source	LED

### Physical

Net Weight (kg)	0.8
-----------------	-----

### Electrical

Power	12
Voltage	220–240
Driver	Integrated
Insulation class	II

