

In Vitro Bollard 1

Flos



No. F018A21A033

Lighting unit with diffuse light for exterior ground installation. Integrated opalescent diffuser and external protection in transparent borosilicate glass. The structure is made of die-cast and extruded aluminium treated with a chemical conversion process for effective resistance to atmospheric agents. The body is powder coated and comes in various finishes. Integrated LED light source with Edge Lighting optical technology to guarantee perfect uniform lighting. Integrated 220–240 V ON/OFF or dimmable electrical power. The unit comes with a watertight plug for connection to the electrical network. The device may be installed on any flooring with anchors. Box for installation on flooring laid over concrete sold separately. 110-V version upon request.

Designed by Philippe Starck



Anthracite



Luminous flux luminaire
667 lm

Beam Angle: 111°

h(m)	E(lx)	D(m)
1	248	2.89
2	62	5.79
3	28	8.68
4	15	11.57
5	10	14.46

Technical

Mounting	Bollard
Flux	667lm
IP Rating	IP66

Photometric

Colour Temp	2700K
Dimming	Non Dimmable
Beam Angle	111
CRI	80

Physical

Net Weight (kg)	2.2
-----------------	-----

Electrical

Power	11
Voltage	220–240
Driver	Integrated
Insulation class	I

