



Beam Angle: 111°

| h(m) | E(lx) | D(m) |
|------|-------|-------|
| 1 | 317 | 2.89 |
| 2 | 79 | 5.79 |
| 3 | 35 | 8.68 |
| 4 | 20 | 11.57 |
| 5 | 13 | 14.46 |

In Vitro Ceiling

Flos

No. F018C35A012

Lighting unit with diffuse light for exterior ceiling installation. Integrated opalescent diffuser and external protection in transparent borosilicate glass. The structure is made of die-cast and extruded aluminium treated with a chemical conversion process for effective resistance to atmospheric agents. The body is powder coated and comes in various finishes. Integrated LED light source with Edge Lighting optical technology to guarantee perfect uniform lighting. Light source included. Ceiling mount. Integrated 220-240 V ON/OFF or dimmable electrical power. 110-V version upon request.

Designed by Philippe Starck



Forest Green

Technical

| | |
|-----------|---------|
| Mounting | Ceiling |
| Flux | 855lm |
| IP Rating | IP66 |

Photometric

| | |
|-------------|--------------|
| Colour Temp | 3000K |
| Dimming | Non Dimmable |
| Beam Angle | 111 |
| CRI | 80 |

Physical

| | |
|-----------------|-----|
| Net Weight (kg) | 2.8 |
|-----------------|-----|

Electrical

| | |
|------------------|------------|
| Power | 13 |
| Voltage | 220-240 |
| Driver | Integrated |
| Insulation class | I |

