



Luminous flux luminaire
244 lm

| Beam Angle: | 47° | |
|-------------|-------|------|
| h(m) | E(lx) | D(m) |
| 1 | 380 | 0.88 |
| 2 | 95 | 1.75 |
| 3 | 42 | 2.63 |
| 4 | 24 | 3.50 |
| 5 | 15 | 4.38 |

Kirk 1

Flos

No. FA54000106

Adjustable projector for installation on ceiling, wall or floor. Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content) and AISI 316L fixing plate. Glass diffuser: extra clear with silkscreen border, fixed to the aluminium through a robotic gluing system. The wiring unit and the emitting unit are connected by an adjustable junction. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65 In compliance with EN60598-1 standards Class of insulation: I Installation: the luminaire is for direct connection to 220-230V with a LED module set to work directly connected to the mains. The luminaire is equipped with an AISI316L stainless steel fixing plate for installation on surface and IP68 connector (6$\leq\varnothing\leq 8\text{mm}$ cable). Ground spike available on request. During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating. Damages on the coating exposed to outdoor conditions or water, could cause corrosion. Chemical substances affect the anticorrosion covering protection.

Designed by Flos Outdoor



Grey

Technical

| | |
|-----------|---------------------------------|
| Mounting | Spike Lights,Wall,Projectors |
| Flux | 244lm |
| IP Rating | IP65 |

Photometric

| | |
|-------------|--------------|
| Colour Temp | 3000K |
| Dimming | Non Dimmable |
| Beam Angle | 50 |
| CRI | 80 |

Physical

Electrical

| | |
|------------------|---------|
| Power | 4.5 |
| Voltage | 220-230 |
| Insulation class | I |



Our product range updates frequently. All product specifications and data are subject to change without warning in order to improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.