



Landlord Spot Ø50 PWM Dimmable Anthracite

Flos

No. F004E22A033



IP65 projector for external use made of turned aluminium body and powered at 24V, and available in 2700K, 3000K and 4000K colour temperatures. With reference to the horizontal axis, the spot can be oriented up to 30° down and up to 90° up. Landlord Spots are available in two sizes, ø40 and ø50 head, both equipped with desmontable front ferrule, in order to install flood lens or up to two honeycombs for maximum visual confort. Landlord Spots can be installed on solid ground spikes, with the possibility of an optional picket, on wall base, or on the innovative tree belt, designed to fix the luminaries directly on tree branches. Spot adjustable head for installation on ground poles or on wall base. Poles and base to be ordered as separated accessories. Heads are equipped with a dismountable ferrule, to insert flood lens or up to two honeycombs, (to be ordered as separate accessories). 24V remote power supply to be ordered separately. Each head comes with a 2000 mm lenght outgoing cable and a wiring kit. - WALL-MOUNTED VERSION: required accessory Wall base code F004Z0400XX - BOLLARD VERSION: required accessory Pole with base code F004Z0100XX/F004Z0200XX/F004Z0300XX - TREE-MOUNTED VERSION: required accessory Tree strap code F004Z070000



Luminous flux luminaire
442 lm

Beam Angle: 26°

h(m)	E(lx)	D(m)
1	1875	0.47
2	469	0.94
3	208	1.41
4	117	1.88
5	75	2.35

Designed by Piero Lissoni



Anthracite

Technical

Mounting	Spike Lights,Bollards,Wall,Projectors
Flux	442lm
IP Rating	IP66

Photometric

Colour Temp	2700K
Dimming	Non Dimmable,DALI PWM,1-10 PWM,DALI
Beam Angle	24
CRI	80

Physical

Net Weight (kg)	0.35
-----------------	------

Electrical

Power	7.20
Voltage	24
Driver	Remote excluded
Insulation class	III



