



## My Way 210x200 Non Dimmable Anthracite

Flos



No. F4356033

Luminaire for outdoor use for built-in installation on the wall with LED light source. Aluminum die-cast body EN AB-47100 (low copper content). High-resistance coating: after a sandblasting treatment of all components to make the surface porous and ensure a greater adhesion of the paint, the external coating is applied with a double layer with epoxy powders according to the QUALICOAT standard. The first layer of epoxy powder gives chemical and mechanical resistance, the second finishing layer of polyester powder ensures resistance to UV rays and atmospheric agents. The painted surfaces are treated with alkaline and acidic washes, then rinsed with demineralized water, subjected to a chemical conversion treatment to protect against oxidation. Frosted polycarbonate diffuser, UV-stabilised, glued to the head of the product to ensure a watertight seal. Integrated 220/240V power supply. Supplied with a double length in plastic material for  $7.5 < \phi < 9.5$  mm section cables.

Designed by Piero Lissoni



Anthracite



Luminous flux luminaire  
668 lm

### Technical

Mounting	Wall
Flux	669lm
IP Rating	IP65

### Photometric

Colour Temp	2700K
Dimming	Non Dimmable
Beam Angle	50
CRI	80

### Physical

Net Weight (kg)	1.44
-----------------	------

### Electrical

Power	13
Voltage	220-240
Driver	Integrated
Insulation class	I

