



Spine T 1 Ultra Hp Elliptical 2

Flos



No. F02523GA018

Energy-efficient Power LED source included Equipped with an integrated snoot for higher visual comfort: the asymmetrical cut visor is available as an accessory. Collimators are available as an accessory to modify the beam opening. Integrated electric power supply 220-240 V ON/OFF. Integrated support for pole fixing, for poles with a diameter between 60 and 120 mm and a maximum thickness of 3 mm. Equipped with a 5 m neoprene cable (10 m upon request) for remote connection. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use. Upon request: 1-10 V or DALI dimmable version with 24 Vdc remote power supply.

Designed by Vincent Van Duysen



Deep Brown



Luminous flux luminaire
624 lm

Beam Angle: 25°

h(m)	E(lx)	D(m)
1	1447	0.45
2	362	0.90
3	161	1.35
4	90	1.79
5	58	2.24

Technical

Mounting	Pole
Flux	624lm
IP Rating	IP66

Photometric

Colour Temp	3000K
Dimming	Non Dimmable
CRI	80

Physical

Net Weight (kg)	1
-----------------	---

Electrical

Power	10.5
Voltage	220-240
Driver	Integrated
Insulation class	I

