

## Spine T 1 Ultra Hp

Flos

No. F02524BA033





Energy-efficient Power LED source included Equipped with an integrated snoot for higher visual comfort: the asymmetrical cut visor is available as an accessory. Collimators are available as an accessory to modify the beam opening. Integrated electric power supply 220-240 V ON/OFF. Integrated support for pole fixing, for poles with a diameter between 60 and 120 mm and a maximum thickness of 3 mm. Equipped with a 5 m neoprene cable (10 m upon request) for remote connection. To guarantee its water tightness, it is recommended to use flexible cables designed for outdoor use. Upon request: 1-10 V or DALI dimmable version with 24 Vdc remote power supply.

Designed by Vincent Van Duysen



Anthracite



Luminous flux luminaire  
730 lm

Beam Angle: 12°

h(m)	E(lx)	D(m)
1	14342	0.20
2	3585	0.41
3	1594	0.61
4	896	0.81
5	574	1.02

### Technical

Mounting	Pole
Flux	730lm
IP Rating	IP66

### Photometric

Colour Temp	4000K
Dimming	Non Dimmable
Beam Angle	12
CRI	80

### Physical

Net Weight (kg)	1
-----------------	---

### Electrical

Power	10.5
Voltage	220-240
Driver	Integrated
Insulation class	I

